

MODEL	SR065Z
Displacement (cc)	6.50
Rated voltage / Frequency	220-240V/50-60 Hz
Refrigerant	R134a
Oil quantity (cm ³)	160
Cooling	Static

BASIC DATA	
Voltage range (V)	220-240V
Application	LBP
Evaporator Temperature Range (°C)	-35/-15
Maximum Ambient Temperature (°C)	43
Expansion Device	Capillary tube
Motor Type	RSIR

PERFORMANCE PARAMETER		
Test conditions	ASHRAE (LBP) -23.3°C	
Test voltage	220V/50 Hz	220V/60 Hz
Cooling capacity (W) (≥95%)	168	185
Cooling capacity (KCAL/h)	144	159
Cooling capacity (BTU/h)	573	631
Rated Watts (W) (≤115%)	140	142
Rated current (A) (≤110%)	1.15	1.05
COP (W/W) (≥95%)	1.20	1.30
EER (BTU/Wh)	4.09	4.45

ACCESSORIES		
DEVICES	Q.ty	Type
Protector	1	SR065Z
Protector buckle	1	
Starting Relay (PTC)	1	PTC 15Ω
Cover	1	
Cover buckle	1	
Cord Lock	1	
Screw for cord lock	2	
Earth screw assembly	1	
Rubber mat	4	
Sleeve	4	

DIMENSIONS TABLE	
Height (mm)	171
(S) Suction tube inner diameter (mm)	∅ 6.2±0.1
(P) Process tube inner diameter (mm)	∅ 6.2±0.1
(D) Discharge tube inner diam (mm)	∅ 5.0±0.1
Compressors per pallet (pcs)	100

Specifications subject to change without notice

COLDEX Compressors

ITALIAN TECHNOLOGY COMPLIANT

SR065Z NO.

220-240V/50-60Hz 1PH

← SUCTION



RoHS



THERMALLY PROTECTED

DO NOT START WITHOUT STARTING DEVICE

MADE IN PRC

